

Meyn neck breaker ECP







Model		12x8″	16x6″	16x6″
Capacity	BPH	9,000	8,500	13,500
Live weight	kg	2.5-5.5	0.5-1.7	1.2-4.0
Number of units		12	16	16
Shackle pitch	inch	8″	6″	6″
Lenght (L)	mm	1,980	1,980	1,980
Width (W1)	mm	780	780	780
Width (W2)	mm	1,450	1,450	1,450
Width (W3)	mm	2,450	2,450	2,450
Height (H)	mm	2,945	2,945	2,945
Weight	kg	920	940	940
Water connection	BSP	3/8″	3/8″	3/8″
Water consumption	m ³ /h	0.5	0.5	0.5
Drain connection	BSP	DN100	DN100	DN100

Head office:

Meyn Food Processing Technology B.V. Westeinde 6, 1511 MA Oostzaan (Amsterdam) P.O. Box 16, 1510 AA Oostzaan The Netherlands **T**: +31 (0)20 2045 000 **F**: +31 (0)20 2045 001 **I**: www.meyn.com



The data published correspond, under reservation of all our rights, to the most recent information at the moment of publication and are subject to future modifications. Meyn reserves the right to modify the construction and the execution of its products at any time. No rights can be derived from this publication.

Meyn neck breaker ECP

- Neck is broken and removed without damaging the neck skin.
- The neck length can be set ver accurately, the neck can even been broken between the shoulders.
- Exact positioning of the bird in the machine results in very high performance.
- Shoulder supports prevent that wings, broken or not, will be damaged by the breaking unit.
- A wide weight range can be processed within one machine setting.







